What is claimed is:

1. An image processing method comprising the steps of:

decoding an image by decomposing the image into multiple color components;

drawing a histogram by calculating the density value frequencies of the image data on the

respective color components which have been obtained as a result of decoding;

calculating a high-density-side peak value and a low-density-side peak value from said

histogram for judging their hierarchical relationship with regard to each of the respective color

components;

counting the number of colors selected from among said multiple color components

whose high-density-side peak values are higher than their low-density-side peak values; and

determining an image which is to become a binarization object based on the number of

color components counted.

2. The image processing method according to claim 1, wherein

the number of colors selected from among said multiple color components whose high-

density-side peak values are higher and the number of colors selected from among said multiple

color components whose low-density-side peak values are higher are compared, and

the outnumbering color components are selected as images which are to become

binarization objects.

3. The image processing method according to claims 1 or 2, wherein

the respective pixels of the images of the respective color components which have been

selected as binarization objects and preliminarily determined threshold levels are compared, and

pixels of the respective color components which exceed said threshold levels are judged to be

either black or white, whereas the other pixels are judged to be the other.

5

4. The image processing method according to claim 1, wherein

when the number of color components whose low-density-side peak values are higher

exceeds the number of color components whose high-density-side peak values are higher, said

color components whose low-density-side peak values are higher are selected as binarization

10 object images, and the white pixels and black pixels of said images are permutated during a

binarization routine.

5. An image processing device comprising:

in an image processing device which processes image data which have been decoded after

15 having been decomposed into multiple color components;

a histogram generation mechanism which generates a density value histogram with regard

to each color component by tabulating inputted pixels in density value-specific fashions;

a peak detection mechanism which detects a low-density-side peak value and a high-

density peak-side value on said density histogram;

20　　　a color component selection unit which compares the hierarchical relationship between

said detected low-density-side peak value and high-density peak-side value with regard to each

color component and which executes a binarization routine based on the comparison results; and

a binarization unit which binarizes the color component image which has been selected

by said color component selection unit.

6. The image processing device according to claim 5 further comprises:

a threshold value designation mechanism which designates a binarization threshold value

5 based on the low-density-side and high-density-side peak values which have been detected by

said peak detection unit is additionally configured.

7. The image processing device according to claims 5 or 6 wherein:

said color component selection unit counts the number of color components whose low-

10 density-side peak values are higher and the number of color components whose high-density-side

peak values are higher, and

said binarization unit judges that, when the number of color components whose high-

density-side peak values are higher is larger, the pixels which exceed said threshold value with

regard to said color components are either white or black, whereas when the number of color

15 components whose low-density-side peak values are higher is larger, the pixels which exceed

said threshold value with regard to said color components are the other.